

SylFlat LED Non Dimmable - Recessed

SylFlat 1000 Round 3000K

0053289



Product features

- Integrated round recessed 165mm diameter LED downlight providing uniform distribution with an opal diffuser, 110° beam angle, 825LM, 12W, 69lm/W, 3000K, CRI80, non-dimmable, IP20, IK06, 25,000hrs (L70)

PRODUCT OVERVIEW

Included lamp	INTEGRATED LED
Technology	LED
Mount	Ceiling recessed
Product name	SylFlat 1000 Round 3000K
Product code	0053289
Housing	Plastic
Fixture rating	Enclosed
General application	Residential & Consumer
Environment	Internal
Certifications	CE
E-number Finland	4274326
Electrical protection	CLASS II
Control gear mounting	Integrated
Control gear type	Electronic
Total power consumption (W)	12
Light colour	Warm white
LOR (%)	100
Luminous flux mounted (lm)	825
Colour temperature (K)	3000
Beam Angle (°)	110
Colour	White
IK rating	IK06
IP rating	IP20
Product EAN number	5410288532899

DATA TABLE

General data

Technology	LED
Mount	Ceiling recessed

SylFlat LED Non Dimmable - Recessed

*SylFlat 1000 Round 3000K***0053289**

Product name	SylFlat 1000 Round 3000K
Product code	0053289
Housing	Plastic
Fixture rating	Enclosed
General application	Residential & Consumer
Environment	Internal
Certifications	CE
E-number Finland	4274326

Optical data

Efficacy (lm/w)	69
Light colour	Warm white
LOR (%)	100
Distribution type	Direct
Luminous flux mounted (lm)	825
Colour temperature (K)	3000
Adjustable chromaticity	N
Beam Angle (°)	110

Electrical data

Efficacy (lm/w)	69
Electrical protection	CLASS II
Control gear mounting	Integrated
Control gear type	Electronic
Drive current (mA)	105
Glow Wire Test (°C)	650
Mains voltage (V)	220-240V~
Total power consumption (W)	12
Inrush Current (A)	2

Lifetime data

Average life (Rated) (h)	25000
---------------------------------	-------

Physical data

Max. Lamp Diameter (mm) - D	165
Colour	White
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Height (mm)	27
IK rating	IK06
IP rating	IP20
Weight (kg)	0.207

SylFlat LED Non Dimmable - Recessed


SylFlat 1000 Round 3000K

0053289

Packaging

Single packaging type	Carton
Packaging single width (cm)	18.7
DUN14 (outer)	15410288532896
Packaging outer height (cm)	39.5
Packaging outer length (cm)	39.8
Units per outer package	16
Packaging single height (cm)	17.8
Packaging single length (cm)	4.4
Product EAN number	5410288532899
Packaging outer width (cm)	21.8

TECHNICAL DRAWINGS





SylFlat LED Non Dimmable - Recessed

SylFlat 1000 Round 3000K


0053289


SYLVANIA 0053289



 This luminaire is compatible with bulbs of the energy classes:

 } **LED**

This luminaire is sold with a bulb of the energy class:

874/2012 

 This luminaire is compatible with bulbs of the energy classes:

 } **LED** 

This luminaire is sold with a bulb of the energy class:

SYLVANIA 0053289 874/2012