

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 4000K

0053303



Product features

- Integrated round surface mounted 220mm diameter LED downlight providing uniform distribution with an opal diffuser, 110° beam angle, 1500LM, 18W, 83lm/W, 4000K, CRI80, non-dimmable, IP20, IK06, 25,000hrs (L70)

PRODUCT OVERVIEW

Product name	SylFlat Surface 1400 Round 4000K
Technology	LED
Mount	Surface mounted
Product code	0053303
Housing	Plastic
Fixture rating	Enclosed
General application	Residential & Consumer
Environment	Internal
Certifications	CE
E-number Finland	4274345
Control gear mounting	Integrated
Control gear type	Electronic
Dimmable	Not dimmable
Electrical protection	CLASS II
Total power consumption (W)	18
Light colour	Neutral white
LOR (%)	100
Luminous flux mounted (lm)	1500
CRI (Ra)	80
Colour temperature (K)	4000
Beam Angle (°)	110
Colour	White
IK rating	IK06
IP rating	IP20
Product EAN number	5410288533032

DATA TABLE

General data

Product name	SylFlat Surface 1400 Round 4000K
---------------------	----------------------------------

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 4000K

0053303

Technology	LED
Mount	Surface mounted
Product code	0053303
Housing	Plastic
Fixture rating	Enclosed
General application	Residential & Consumer
Environment	Internal
Certifications	CE
E-number Finland	4274345

Optical data

Efficacy (lm/w)	83
Adjustable chromaticity	N
Light colour	Neutral white
LOR (%)	100
Distribution type	Direct
Luminous flux mounted (lm)	1500
CRI (Ra)	80
Colour temperature (K)	4000
Beam Angle (°)	110

Electrical data

Efficacy (lm/w)	83
Control gear mounting	Integrated
Control gear type	Electronic
Drive current (mA)	150
Dimmable	Not dimmable
Glow Wire Test (°C)	650
Electrical protection	CLASS II
Mains voltage (V)	220-240V~
Total power consumption (W)	18
Inrush Current (A)	2

Lifetime data

Average life (Rated) (h)	25000
---------------------------------	-------

Physical data

Max. Lamp Diameter (mm) - D	220
Colour	White
Diffuser finish	Opal
Diffuser material	Polycarbonate
Nominal Product Height (mm)	40
IK rating	IK06

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 4000K


0053303

IP rating	IP20
Weight (kg)	0.218

Packaging

Single packaging type	Carton
Packaging single width (cm)	17.0
DUN14 (outer)	15410288533039
Packaging outer height (cm)	18.5
Packaging outer length (cm)	69.5
Units per outer package	16
Packaging single height (cm)	17.0
Packaging single length (cm)	42.0
Product EAN number	5410288533032
Packaging outer width (cm)	68.5

TECHNICAL DRAWINGS





SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 4000K


0053303


SYLVANIA 0053303



 This luminaire is compatible with bulbs of the energy classes:

 } **LED**

This luminaire is sold with a bulb of the energy class:

874/2012 

 This luminaire is compatible with bulbs of the energy classes:

 } **LED** 

This luminaire is sold with a bulb of the energy class:

SYLVANIA 0053303 874/2012