Technical specification

Create a graphic wall decoration with Stick, Which slender lines naturally slides underneath Each other for a creative setting, showing the beauty of indirect light.

Technical data

Material Aluminum

Colour White, Black, Gold

Light Source LED. Average lifetime 50.000 hrs.

Voltage 230-240 V Electronic Control gear Color temperature 3000K CRI (Ra) 80>



NOTE:

5 years warranty on LED light source.

Can be connected to mains (electricity) from both bases

*Gold colour recommended for indoor use only.

"Gold colour recommended for indoor use only.									
STICK 120		WALL AND CEILIN	INDIRECT LIGHT OUTDOOR	ECO IP 54	650° F CE				
CODE	MEASURE mm	LIGHT SOURCE		MOUNTING	44mm				
256500 White	L1200XW50XD44	LED 25W		Wall/ceiling					
256501 Black	L1200XW50XD44	LED 25W		Wall/ceiling	8-200mm				
256503 Gold*	L1200XW50XD44	LED 25W		Wall/ceiling	E THE STATE OF THE				
					8.				

STICK 150

CODE	MEASURE mm	LIGHT SOURCE	MOUNTING	South Section 1
256504 White	L1500XW50XD60	LED 30W	Wall/ceiling	
256505 Black	L1500XW50XD60	LED 30W	Wall/ceiling	O EDONAL
256507 Gold*	L1500XW50XD60	LED 30W	Wall/ceiling	E 31E
				Aftr

STICK 180

MEASURE mm	LIGHT SOURCE		MOUNTING	Porton .
L1800XW50XD76	LED 36W		Wall/ceiling	ones (S
L1800XW50XD76	LED 36W		Wall/ceiling	0)188
L1800XW50XD76	LED 36W		Wall/ceiling	. Ju
				Manual Atlanta
	L1800XW50XD76 L1800XW50XD76	L1800XW50XD76 LED 36W L1800XW50XD76 LED 36W	L1800XW50XD76 LED 36W L1800XW50XD76 LED 36W	L1800XW50XD76 LED 36W Wall/ceiling L1800XW50XD76 LED 36W Wall/ceiling L1800XW50XD76 LED 36W Wall/ceiling

