

SmartBright LED Downlight

DN061B 1xDLED/840 WH

When switching from conventional CFL to LED lighting, most customers want a green solution with an attractive total cost of ownership. SmartBright LED Downlight is characterized by low cost and high efficiency, providing the end-user with the perfect green light fixture.

Product data

• General information

Product family code Number of light sources Lamp family code Light source color Protection class IEC Ingress protection code

Color Flammability mark DN061B [DN061B] 1 [1 pc]

DLED [DLED Module] 840 [840 white] CLI [Safety class I] IP20 [Finger-protected]

WH [White]

F [For mounting on normally flammable surfaces]

• Electrical

Input voltage 220-240 V [220 to 240 V] Input frequency 50-60 Hz [50 to 60 Hz]

• Initial perform. (IEC compliant)

Initial input power 10 W [10 W]

• Product Data

Order code Full product code Full product name Order product name Pieces per pack Packs per outerbox Bar code on pack -EAN1 Bar code on outerbox - EAN3 Logistic code(s) -

Net weight per piece

911401700762 911401700762

DN061B 1xDLED/840 WH DN061B 1xDLED/840 WH

12

000000000000

000000000000

911401700762

0.201 kg










SmartBright LED Downlight

Dimensional drawing



DN061B 1xDLED/840 WH



 $\ \odot$ 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.