



LED PAR16

Model No.: LR2104DG-WFL
Voltage (V): 220-240
Rated Wattage (W): 4.0



Lamp Base	Rated Lamp Life (hrs)	Diameter (mm)	Length (mm)	Total Luminous Flux (lm)	Rated Luminous Flux in 90° cone (lm)	Rated Beam Angle (°)	Max. Luminous Intensity (cd)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 100% of the Full Light Output(sec)	Switching Cycles (times)	Colour Consistency (SDCM)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
				lm	Φ_{use}		cd	CRI	PF				SDCM		
Warm White (2800K)															
E14	15,000	50	76	250	220	35	560	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+
Cool White (4000K)															
E14	15,000	50	76	250	220	35	560	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+
Day Light (6500K)															
E14	15,000	50	76	250	220	35	560	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+



Operating Temperature (°C) :

-30 to +40



Mercury Content (mg):

N/A



Spectral power distribution



2800K




4000K



6500K



LED PAR16



Conventional PAR16