



LED PAR16

Model No.: LR2104DG-SWFL
Voltage (V): 220-240
Rated Wattage (W): 4.0



Lamp Base	Rated Lamp Life (hrs)	Diameter (mm)	Length (mm)	Total Luminous Flux (lm)	Rated Luminous Flux in 90° cone (lm)	Rated Luminous Flux in 120° cone (lm)	Rated Beam Angle (°)	Max. Luminous Intensity (cd)	Colour Rendering Index (Ra)	Power Factor	Starting Time (sec)	Warm-up Time Up to 100% of the Full Light Output(sec)	Switching Cycles (times)	Colour Consistency (SDCM)	Lumen Maintenance at the End of Lamp Life (%)	Energy Label (EEL)
				lm	Φ_{use}	Φ_{use}	A	cd	CRI	PF				SDCM		
Warm White (2800K)																
GU10	15,000	50	57	250	220	230	90	160	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+
Cool White (4000K)																
GU10	15,000	50	57	250	220	230	90	160	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+
Day Light (6500K)																
GU10	15,000	50	57	250	220	230	90	160	80	>0.4	<0.5	Instant full light	>1,000,000	<6	≥70	A+

Operating Temperature (°C) : -30 to +40
Mercury Content (mg): N/A

Spectral power distribution

