

MR16/GU10/PAR16

7MR16/F35 3000 DIM AF2 10/1

Philips MR16 Dimmable LED Lamps provide ambient level light to illuminate hard to maintain applications. Increased transformer compatability allows for operation on a wider range of transformers. Available in dimmable and non-dimmable versions, these lamps are ideal for track and open recessed fixtures in retail, hospitality and residential spaces.

Product data

• General Information

 Cap-Base
 GU5.3 [GU5.3]

 Nominal Lifetime (Nom)
 40000 h

 Switching Cycle
 50000X

 Technical Type
 7-35W

• Light Technical

Color Code 830 [CCT of 3000K] Beam Angle (Nom) Light Distribution 36D [Medium beam] Luminous Flux 440 lm (Nom) Luminous Flux 440 lm (Rated) (Nom) Luminous Intensity 1200 cd (Nom) Color Designation White (WH) Rated Beam Angle 3000 K Correlated Color Temperature (Nom) Luminous Efficacy 58.00 lm/W (rated) (Nom) Color Consistency 6 steps Color Rendering Index (Nom) LLMF At End Of 70 % Nominal Lifetime (Nom) Luminous Flux In 90° 405 lm

• Operating and Electrical

Cone (Rated)

Power (Rated) 7 W (Nom)

Lamp Current (Nom) 720 mA
Wattage Equivalent 35 W
Starting Time (Max) 0.5 s
Warm Up Time To instant full light
60% Light (Nom)
Power Factor (Nom) 0.7
Voltage (Nom) 12 V

• Temperature

T-Case Maximum 102 °C (Max)
T-Case Maximum 102 °C (Nom)

Controls and Dimming

Dimmable Yes

Approval and Application

Suitable For Accent Yes
Lighting
Energy Efficiency A
Label (EEL)
Energy Consumption 8 kWh
kWh/1000 h


• Product Data



Material Nr. (12NC) 929001153204


Net Weight (Piece) 0.045 kg

Dimensional drawing




LED D 7-35W 830 MR16 36D

Product	D	С
7MR16/F35 3000 DIM AF2 10/1	50.5 mm	50.5 mm



Photometric data





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.