

MASTER LEDspot LV

MAS LEDspotLV D 8.0-50W 827 MR16 36D

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot and general lighting applications in the hospitality industry. It is particularly suited to public areas such as receptions, lobbies, corridors, stairwells and washrooms, where the light is on all the time. The robustly designed MASTER LEDspot offers a choice of beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

Product data

• General Information

Cap-Base GU5.3 [GU5.3]
Bulb Shape MR16 [2inch/50mm]
Nominal Lifetime (Nom)
Switching Cycle 50000X
Technical Type 8-50W

• Light Technical

Colour Code 827 [CCT of 2700K] Beam Angle (Nom) Light Distribution 36D [Medium beam] Luminous Flux 635 lm (Nom) Luminous Flux 635 lm (Rated) (Nom) 1650 cd Luminous Intensity (Nom) Warm White (WW) Colour Designation Rated Beam Angle 2700 K Colour Temperature, horizontal (Nom) 78 lm/W Luminous Efficacy (rated) (Nom) Color Consistency 6 steps Colour Rendering 80 Index horiz (Nom) LLMF At End Of 70 % Nominal Lifetime (Nom) Luminous Flux In 90° 621 lm Cone (Rated)

• Operating and Electrical

Input Frequency 50 to 60 Hz Power (Rated) 8 W (Nom) Lamp Current (Nom) 900 mA Wattage Equivalent 50 W Starting Time (Max) 0.5 s Warm Up Time To instant full light 60% Light (Nom) Power Factor (Nom) 0.7 Voltage (Nom) 12 V

• Temperature

T-Case Maximum 105 °C (Nom)

• Controls and Dimming

Dimmable Yes

Approval and Application

Suitable For Accent Yes
Lighting
Energy Efficiency A+
Label
Energy Consumption 8 kWh/1000 h



MASTER LEDspot LV

• Product Data

Full product code 871869651536500

MAS LEDspotLV D 8.0-50W 827 Order product name

MR16 36D 8718696515365

EAN/UPC - Product 51536500 Order code

Warnings and Safety


 \bullet Operating temperature range is between -20° C and 45° C ambient

1 Numerator -Quantity Per Pack 10 Numerator - Packs

per outer box Material Nr. (12NC) Net Weight (Piece) 929001150102 0.045 kg


- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights

Dimensional drawing




LED D 8-50W 827 MR16 36D

Product	D	С
MAS LEDspotLV D 8.0-50W 827 MR16 36D	51 mm	55 mm



Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.