

# SylFlat LED Non Dimmable - Recessed

*SylFlat 1000 Round 4000K*

**0053294**



## Product features

- Integrated round recessed 165mm diameter LED downlight providing uniform distribution with an opal diffuser, 110° beam angle, 960LM, 13W, 74lm/W, 4000K, CRI80, non-dimmable, IP20, IK06, 25,000hrs (L70)

## PRODUCT OVERVIEW

Included lamp	INTEGRATED LED
Product name	SylFlat 1000 Round 4000K
E-number Finland	4274332
Technology	LED
Mount	Ceiling recessed
Housing	Plastic
Product code	0053294
Environment	Internal
Fixture rating	Enclosed
General application	Residential & Consumer
Certifications	CE
Control gear mounting	Integrated
Control gear type	Electronic
Dimmable	Not dimmable
Electrical protection	CLASS II
Total power consumption (W)	12
Beam Angle (°)	110
Light colour	Neutral white
LOR (%)	100
Luminous flux (lm)	960
Luminous flux mounted (lm)	960
CRI (Ra)	80
Colour temperature (K)	4000
Colour	White
IK rating	IK06
IP rating	IP20
Product EAN number	5410288532943

## DATA TABLE

# SylFlat LED Non Dimmable - Recessed

*SylFlat 1000 Round 4000K*

**0053294**

## General data

<b>Product name</b>	SylFlat 1000 Round 4000K
<b>E-number Finland</b>	4274332
<b>Technology</b>	LED
<b>Mount</b>	Ceiling recessed
<b>Housing</b>	Plastic
<b>Product code</b>	0053294
<b>Environment</b>	Internal
<b>Fixture rating</b>	Enclosed
<b>General application</b>	Residential & Consumer
<b>Certifications</b>	CE

## Optical data

<b>Beam Angle (°)</b>	110
<b>Adjustable chromaticity</b>	N
<b>Light colour</b>	Neutral white
<b>LOR (%)</b>	100
<b>Luminous flux (lm)</b>	960
<b>Efficacy (lm/w)</b>	80
<b>Luminous flux mounted (lm)</b>	960
<b>Distribution type</b>	Direct
<b>CRI (Ra)</b>	80
<b>Colour temperature (K)</b>	4000

## Electrical data

<b>Control gear mounting</b>	Integrated
<b>Control gear type</b>	Electronic
<b>Dimmable</b>	Not dimmable
<b>Drive current (mA)</b>	105
<b>Glow Wire Test (°C)</b>	650
<b>Electrical protection</b>	CLASS II
<b>Mains voltage (V)</b>	220-240V~
<b>Inrush Current (A)</b>	2
<b>Total power consumption (W)</b>	12
<b>Efficacy (lm/w)</b>	80

## Lifetime data

<b>Average life (Rated) (h)</b>	25000
---------------------------------	-------

## Physical data

<b>Colour</b>	White
<b>Diffuser finish</b>	Opal

# SylFlat LED Non Dimmable - Recessed

*SylFlat 1000 Round 4000K*


**0053294**

Diffuser material	Polycarbonate
Nominal Product Height (mm)	27
IK rating	IK06
IP rating	IP20
Weight (kg)	0.207
Max. Lamp Diameter (mm) - D	165

## Packaging

Single packaging type	Carton
Packaging single width (cm)	18.7
Units per outer package	16
Packaging single length (cm)	4.4
Packaging single height (cm)	17.8
Product EAN number	5410288532943
DUN14 (outer)	15410288532940
Packaging outer height (cm)	39.5
Packaging outer length (cm)	39.8
Packaging outer width (cm)	21.8

## TECHNICAL DRAWINGS




## SylFlat LED Non Dimmable - Recessed

*SylFlat 1000 Round 4000K*

**0053294**

**SYLVANIA**
0053294



This luminaire is compatible with bulbs of the energy classes:

A<sup>++</sup>

A<sup>+</sup>

A

B

C

D

E


}


L

E

D

This luminaire is sold with a bulb of the energy class:

874/2012




This luminaire is compatible with bulbs of the energy classes:

A<sup>++</sup>

A<sup>+</sup>

A

B

C

D

E


}

L

E

D

This luminaire is sold with a bulb of the energy class:



**SYLVANIA**
0053294
874/2012