

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 3000K

0053299



Product features

- Integrated round surface mounted 220mm diameter LED downlight providing uniform distribution with an opal diffuser, 110° beam angle, 1300LM, 18W, 72lm/W, 3000K, CRI80, non-dimmable, IP20, IK06, 25,000hrs (L70)

PRODUCT OVERVIEW

| | |
|------------------------------------|----------------------------------|
| Product name | SylFlat Surface 1400 Round 3000K |
| Technology | LED |
| Mount | Surface mounted |
| Product code | 0053299 |
| Housing | Plastic |
| Fixture rating | Enclosed |
| General application | Residential & Consumer |
| Environment | Internal |
| Certifications | CE |
| E-number Finland | 4274339 |
| Control gear mounting | Integrated |
| Control gear type | Electronic |
| Dimmable | Not dimmable |
| Electrical protection | CLASS II |
| Total power consumption (W) | 18 |
| Light colour | Warm white |
| LOR (%) | 100 |
| Luminous flux mounted (lm) | 1300 |
| CRI (Ra) | 80 |
| Colour temperature (K) | 3000 |
| Beam Angle (°) | 110 |
| Colour | White |
| IK rating | IK06 |
| IP rating | IP20 |
| Product EAN number | 5410288532998 |

DATA TABLE

General data

| | |
|---------------------|----------------------------------|
| Product name | SylFlat Surface 1400 Round 3000K |
|---------------------|----------------------------------|

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 3000K

0053299

| | |
|----------------------------|------------------------|
| Technology | LED |
| Mount | Surface mounted |
| Product code | 0053299 |
| Housing | Plastic |
| Fixture rating | Enclosed |
| General application | Residential & Consumer |
| Environment | Internal |
| Certifications | CE |
| E-number Finland | 4274339 |

Optical data

| | |
|-----------------------------------|------------|
| Efficacy (lm/w) | 72 |
| Adjustable chromaticity | N |
| Light colour | Warm white |
| LOR (%) | 100 |
| Distribution type | Direct |
| Luminous flux mounted (lm) | 1300 |
| CRI (Ra) | 80 |
| Colour temperature (K) | 3000 |
| Beam Angle (°) | 110 |

Electrical data

| | |
|------------------------------------|--------------|
| Efficacy (lm/w) | 72 |
| Control gear mounting | Integrated |
| Control gear type | Electronic |
| Drive current (mA) | 150 |
| Dimmable | Not dimmable |
| Glow Wire Test (°C) | 650 |
| Electrical protection | CLASS II |
| Mains voltage (V) | 220-240V~ |
| Total power consumption (W) | 18 |
| Inrush Current (A) | 2 |

Lifetime data

| | |
|---------------------------------|-------|
| Average life (Rated) (h) | 25000 |
|---------------------------------|-------|

Physical data

| | |
|------------------------------------|---------------|
| Max. Lamp Diameter (mm) - D | 220 |
| Colour | White |
| Diffuser finish | Opal |
| Diffuser material | Polycarbonate |
| Nominal Product Height (mm) | 40 |
| IK rating | IK06 |

SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 3000K


0053299

| | |
|--------------------|-------|
| IP rating | IP20 |
| Weight (kg) | 0.218 |

Packaging

| | |
|-------------------------------------|----------------|
| Single packaging type | Carton |
| Packaging single width (cm) | 17.0 |
| DUN14 (outer) | 15410288532995 |
| Packaging outer height (cm) | 18.5 |
| Packaging outer length (cm) | 69.5 |
| Units per outer package | 16 |
| Packaging single height (cm) | 17.0 |
| Packaging single length (cm) | 42.0 |
| Product EAN number | 5410288532998 |
| Packaging outer width (cm) | 68.5 |

TECHNICAL DRAWINGS





SylFlat LED Non Dimmable - Surface

SylFlat Surface 1400 Round 3000K


0053299


SYLVANIA 0053299



 This luminaire is compatible with bulbs of the energy classes:

 } **LED**

This luminaire is sold with a bulb of the energy class:

874/2012 

 This luminaire is compatible with bulbs of the energy classes:

 } **LED** 

This luminaire is sold with a bulb of the energy class:

SYLVANIA 0053299 874/2012