PHILIPS Lighting



SmartBright LED Floodlight

BVP173 LED66/CW 70W WB GREY L1000

LED module 6600 lm

The SmartBright LED Floodlight is a versatile floodlight engineered to deliver significant energy savings, an ideal solution for diverse floodlighting applications. The product is also designed to meet relevant performance and safety standards, offering you reliable and long-lasting performance.

Product data

| General Information | |
|-----------------------------|-------------------------------------------------|
| Lamp family code | LED66 [LED module 6600 lm] |
| Lamp colour code | 757 cool white |
| Light source replaceable | No |
| Driver included | Yes |
| Optical cover/lens type | PC-UV [Polycarbonate bowl/cover UV-resistant] |
| Luminaire light beam spread | 30° x 80° |
| Connection | Flying leads/wires |
| Cable | Cable 1.0 m without plug (C1K) |
| Protection class IEC | Safety class I (I) |
| Flammability mark | F [For mounting on normally flammable surfaces] |
| CE mark | CE mark |
| Constant light output | No |
| Number of products on MCB | 37 |
| LED engine type | LED |
| | |
| Operating and Electrical | |
| Input voltage | 220 to 240 V |

| Input frequency | 50 or 60 Hz |
|-----------------------------|-----------------------------------|
| Inrush current | 9.2 A |
| Inrush time | 0.066 ms |
| Power factor (min.) | 0.9 |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |
| Mechanical and Housing | |
| Housing material | Aluminum die-cast |
| Optical cover/lens material | Polycarbonate |
| Mounting device | MBA [Mounting bracket adjustable] |
| Optical cover/lens shape | Flat |
| Optical cover/lens finish | Frosted |
| Overall length | 300 mm |
| Overall width | 190 mm |
| Overall height | 40 mm |
| | |


SmartBright LED Floodlight

| Effective projected area | 0.049 m² |
|--------------------------------|----------------------------------------------|
| | |
| Approval and Application | |
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK07 [2 J reinforced] |
| | |
| Initial Performance (IEC Com | pliant) |
| Initial luminous flux | 6650 lm |
| Luminous flux tolerance | +/-10% |
| Initial LED luminaire efficacy | 95 lm/W |
| Lamp colour temperature | 5700 K |
| Colour Rendering Index | >70 |
| Initial chromaticity | SDCM<7 |
| Initial input power | 70 W |
| Power consumption tolerance | +/-10% |
| | |

| Application Conditions | |
|---------------------------------|-----------------------------------|
| Maximum dimming level | Not applicable |
| | |
| Product Data | |
| Full product code | 871016332095399 |
| Order product name | BVP173 LED66/CW 70W WB GREY L1000 |
| EAN/UPC - product | 8710163320953 |
| Order code | 911401690704 |
| Numerator - quantity per pack | 1 |
| Numerator - packs per outer box | 8 |
| Material no. (12NC) | 911401690704 |
| Net weight (piece) | 1.800 kg |
| | |



Dimensional drawing



BVP173/174/176 Smartbright



© 2018 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2018, June 9 - data subject to change