



requires

.hub



works with

.control




## Product Description:

Utilite™ 30W Polycarbonate IP65 Round Utility Bulkhead


Utilite™ is a powerful yet energy efficient alternative to standard bulkhead utility luminaires. Designed specifically for LED technology, their impact resistant polycarbonate housing provides a tough exterior making them ideal for all basic industrial, commercial and residential installations.

| SKU Code    | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type     |
|-------------|---------|--------|--------|-------------|------------|---------------|--------------|
| EN-BH130/40 | 30      | 4000   | 2800   | 94          | 120        | White         | Non Dimmable |

## Line Drawing



## Polar Curve



## Color

## Product Features:

- IP65 rated polycarbonate white housing
- Integrated driver for slim profile
- Wall or ceiling mountable with 20mm knockouts
- Available in a range of sizes and shapes to suit multiple installation requirements
- Interchangeable bezel options available (sold separately)
- Impact resistant - IK06 rating
- 1.5kV surge protection
- 3 year warranty

## Product Specs:

|                          |             |                          |         |
|--------------------------|-------------|--------------------------|---------|
| Input Voltage            | 220~240V AC | Input Frequency          | 50/60HZ |
| Power Factor             | 0.5         | IP Rating                | IP65    |
| Lifetime L70 (hrs)       | 25000       | IK Rating                | IK06    |
| Lamp Base                | None        | Height (mm)              | 80      |
| Overall Diameter (mm)    | 300         | Weight (Kg)              | 0.921   |
| Product Type             | Bulkheads   | Operating Temp. (Min) °C | -20°C   |
| Operating Temp. (Max) °C | 40°C        |                          |         |

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.