



SmartBright Suspension

RC095V LED30S/865 PSU W12L120 Grey

Linear suspension solution with affordable price

Product data

General Information	
Beam angle of light source	_ °
Light source color	865 cool daylight
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Symmetrical
Optical cover/lens type	Polystyrene bowl/cover prismatic
Luminaire light beam spread	120°
Control interface	-
Connection	-
Cable	Cable 1.0 m without plug
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	-
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	210
RoHS mark	RoHS mark

Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Inrush current	6.7 A
Inrush time	0.0072 ms
Power Factor (Min)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Aluminum
Reflector material	-
Optic material	Polystyrene
Optical cover/lens material	Polystyrene
Fixation material	Stainless steel
Optical cover/lens finish	Frosted
Overall length	600 mm
Overall width	120 mm
Overall height	65 mm

SmartBright Suspension

Color	Gray
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Initial Performance (IEC Complian	t)
Initial luminous flux (system flux)	1500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	88 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	≤5
Initial input power	17 W
Power consumption tolerance	+/-10%

25000 h

Application Conditions	
Ambient temperature range	-10 to +35 °C
Maximum dim level	Not applicable
Suitable for random switching	No
Product Data	
Full product code	692382862895600
Order product name	RC095V LED30S/865 PSU W12L120 Grey
EAN/UPC - Product	6923828628956
Order code	911401723482
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401723482
Net Weight (Piece)	1.919 kg

650°C 308 ₽ 20 ₩ 03 (=)

Dimensional drawing

Median useful life L70B50

Over Time Performance (IEC Compliant)



SmartBright Troffer RC098V



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2019, September 13 - data subject to change