

MR16 8W GU5.3 2800K DIMMABLE



Product Code:

ER203080/dm-HRv00-WF+GU5.3+828+AC012

| Electrical Data | |
|--|---------------------|
| Voltage (V) | AC 12V |
| Power Factor | >0.9 |
| Starting Time (sec) | <0.5 |
| Warm-up Time Up to 100% of the Full Light Output (sec) | Instant full light |
| Product Data | |
| Lamp Base | GU5.3 |
| Product Wattage (W) | 8 |
| Equivalent Wattage (W) | 46 |
| Reflector | MR16 |
| Beam Angle (°) | 36 |
| Colour Temperature (K) | Warmwhite (2800K) |
| Colour Render Index (Ra) | Ra80 |
| Dimmable | 100-10% |
| Energy Label | A |
| Operating Temperature | -30 ° C to +40 ° C |
| Switching Cycles (times) | >1,000,000 |
| Mercury Content (mg) | No |
| Weight (g) | 55 |
| Application | Retail, Hospitality |
| Performance Data | |
| Max. Luminous Intensity (cd) | 1800 |
| Total Luminous Flux (lm) | 600 |
| Rated Life (hrs) | 25000 |
| Lumen Maintenance at the End of Lamp Life (%) | 90 |
| Product Dimensions | |
| Diameter (mm) | 50 |
| Length (mm) | 49 |
| Remarks: The rated lamp life, rated luminous flux in 90 ° cone, total luminous flux, rated beam angle and rated wattage are equivalent to their nominal values shown on product packaging. | |

Product Code: ER203080/dm-HRv00-WF+GU5.3+828+AC012

MEGAMAN® 2005-2020. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc

Technologies



Being able to adjust your LEDs with wide selection of dimming range from 100% to 10% or 20% for perfect atmosphere and/or scene setting – warm and bright, dim and cozy.